

PX HYDR O PLUG

Fast-setting hydraulic-cement mortar

DESCRIPTION

PX Hyrdo Plug is a durable, fast-setting hydraulic-cement mortar that stops flowing water through holes and cracks in concrete and masonry surfaces. PX Hyrdo Plug will not shrink or oxidize.

FEATURES/BENEFITS

- Single component; just add water and use
- Expands as it sets, bonds strongly to concrete and makes watertight repairs
- Sets in approximately 3 – 5 minutes, stops flowing water fast.

SPECIFICATIONS

Yield

One 50 lb (22.7 kg) pail yields approximately 0.43 cubic feet

One pound (0.45 kg) will fill 15.6 cubic inches

Color: Concrete gray

APPLICATION

Recommended for use in:

- Basement and masonry cracks
- Floor and wall joints
- Manholes
- Sewer pipes
- Tunnels
- Swimming pools
- Below-grade foundations

Surface Preparation

1. For best results, enlarge crack to a width and depth of 3/4" (19 mm); cut square or undercut. Do not cut in a "V" shape.
2. Clean the substrate of all grease, wax, oil, contaminants, and curing compounds. Remove all weak, contaminated, or deteriorated concrete.
3. Saturate the surface with water. PX Hyrdo Plug will cure in the presence of running water.)

Mixing

Add a small amount of clean water to PX Hyrdo Plug and mix to a putty consistency. Use an approximate ratio of 20% – 25% water to product (by weight). Mix only enough material that can be placed in 2 minutes: 9.5 – 12 pints water to 50 lbs of product.

Application

1. For vertical and moving-water applications, hold product firmly in place until it reaches final set, in approximately 3 minutes.
2. Temperatures below 60° F (16° C) may delay set. Use hot water and warm material to speed setting time. In temperatures above 80° F (27° C) protect the material from hot sun and use cold water to slow setting time.

Curing

PX Hyrdo Plug cures and continues to gain strength as long as it remains damp. Keep the material damp for a minimum of 30 minutes. The product obtains optimal strength when wet cured for up to 2 days.

PACKAGING

50 lb (22.7 kg) pails

LIMITATIONS/PRECAUTIONS

Do not place at temperatures below 40°F (5°C) or if the temperature is expected to fall below 40°F (5°C) in the next twenty-four hour period.

SHELF LIFE

1 year when properly stored in unopened containers in a clean, dry area between 45°F and 90°F (7°C and 32°C).

WARRANTY

NOTICE-READ CAREFULLY CONDITIONS OF SALE

Manufacturer offers this product for sale subject to and limited by the warranty which may only be varied by written agreement of a duly authorized corporate officer of Manufacturer. No other representative of or for Manufacturer is authorized to grant any warranty or to waive limitation of liability set forth below.

WARRANTY LIMITATION

Manufacturer warrants this product to be free of manufacturing defects. If the product when purchased was defective and was within use period indicated on container or carton, when used, Manufacturer will replace the defective product with new product without charge to the purchaser. Manufacturer makes no other warranty, either expressed or implied, concerning this product. There is no warranty of merchantability. NO CLAIM OF ANY KIND SHALL BE GREATER THAN THE PURCHASE PRICE OF THE PRODUCT IN RESPECT OF WHICH DAMAGES ARE CLAIMED.

INHERENT RISK

Purchaser assumes all risk associated with the use or application of the product.

Balbeck S.A.
Soluciones Innovadoras para la Construcción



De Repuestos Gigantes Casa de portones
blancos 150 m norte en Barrio San Jose
Curridabat
Tel: (506) 22 72-34-24 – Fax: (506) 22 72-34-80